

OFDC - A4 Outdoor fiber distribution closure

An ideal solution for FTTH networks, the OFDC-A4 gel sealed closure provides an ideal connection point for distribution & drop cables.

The closure can be used in aerial, pedestal and underground (up to 2 meters) environments.

The closure provides separate compartments for each functional area of pigtail storage, tube breakout, splicing, and patching to drop cables. Individual access is provided to a patching compartment, allowing connection to drop cables without disturbance of fibers stored in other compartments.

Connection to distribution cables is via Tyco Electronics' Xpres-drop Cable (SC/UPC, SC/APC connector footprints).

The gel seals used for both closure and cables are fully re-useable and make re-entry quick and easy.

Features:

- Compact design
- Separate compartments for functional area of pigtail storage, tube breakout and splicing, and patching to drop cables
- Individual access to drop cable connection area
- Drop cable terminated in the closure using Tyco Electronics' Xpres-drop Cable (SC/UPC, SC/APC connector footprints)
- Entire fiber management section can be removed from closure body
- 12F fusion splice or MPO/MTP connectivity for fiber termination
- Also suitable for housing optical splitters
- Two cable ports (10-12mm)
 Four drop cable ports (3-5mm)
- · No special installation tools required






Kit content

- Closure with fiber organizer
- · Main cable and drop cable seal and termination devices
- · 12F fusion splice holder or MPO/MTP adapter


Dimension and capacities



Length × Width × Height (mm)	211 × 119 × 76
Cable diameter for main cables (mm)	10 - 12
Cable diameter for drop cables (mm)	3 - 5

Universal splice holder for 24 RECORDsplice or 48 SMOUV (45mm) splices

Xpres version



TE (logo) and TE Connectivity are trademarks.

Users should rely on their own judgment to evaluate the suitability of a product for a certain purpose and test each product for its intended application. TE Connectivity's only obligations are those stated in TE Connectivity's Standard Terms and Conditions of Sale. TE Connectivity expressly disclaims any implied warranty regarding the information contained herein, including, but not limited to, the implied warranties of merchantability or fitness for a particular purpose.

Tyco Electronics (Shanghai) Co., Ltd. 287 Qinjiang Road, Shanghai, 200233 China Product Information Center 86-4008206015 www.te.com/telecom AsiaPacTelecomMarketing@te.com TC-2089/DS/1-03/10

